

Installation Instructions

Linkin' Log

Part # AP031



ID SCULPTURE

PLAY. CLIMB. EXPLORE.

591 South Boulevard Street
Gunnison, Colorado 81230
info@idsculpture.com
970-641-1747

Specifications: Linkin' Log

- Material: Concrete
- Approximate Uninstalled Size: 7'-2" x 3'-0" x 3'-4" Tall
- Approximate Weight: 2,700 Lbs
- Maximum Fall Height: 2'-4" (assumes 1' of safety surfacing)
- Age Group: 2-5 Years Old

Required Parts (included):

- Linkin' Log GFRC Sculpture
- "Linkin' Log" Drawing Set


Recommended Equipment (not included):

- 6' Lifting straps: 4ct
- Large Adjustable Crescent Wrench
- Lift: Reach Type Forklift 4,000lb Capacity or Crane
- 1/2" Quick Link: 4ct




Important Notes:

- *Warning: Installation over a hard surface such as asphalt, or packed earth may result in serious injury or death from falls.*
- *It is the responsibility of the installer to ensure all components are installed in compliance with ASTM F-1487.*
- *All site built footings should be allowed to cure for a minimum of 48 hours prior to installation.*



Typical Wedge Anchor Installation



Section

Installation Instructions

Linkin' Log

Part # AP031



591 South Boulevard Street
Gunnison, Colorado 81230
info@idsculpture.com
970-641-1747

PRE-INSTALL CHECKLIST

Please review prior to ordering and installing ID Sculpture products.

- ☐ 1. Verify that you have the recommended lifting equipment to unload and install your component, as specified by the installation instructions. Please check the installation instructions for the weight of each component and shipping dimensions.
- ☐ 2. Develop a proper plan to access the site and control access prior to opening.
- ☐ 3. Call your local utilities to locate any potential existing below grade equipment?
- ☐ 4. FOR ALL SCULPTURES: Verify you have accounted for adjustments to the footing depth based on your choice of safety surfacing material. Footing depth must be adjusted to compensate for the depth/thickness requirements of the selected safety surfacing (*see diagrams below*). Layout drawings show the uninstalled dimensions of the component. If you require a modification to a standard component, please notify ID Sculpture when placing your order. *Additional charges may apply.*



*Critical Fall Height (CFH)

- ☐ 5. Verify that you have installed any required footings prior to the arrival of your sculptures. Please note, footings should be allowed to cure for a minimum of 7 days.

Important Safety Note:

Please install and maintain adequate protective surfacing under and around your equipment. Never let children play on the equipment before protective surfacing is installed. Please consult ASTM F1487 for more information.

Installation Instructions

Linkin' Log


Part # AP031



591 South Boulevard Street
Gunnison, Colorado 81230
info@idsculpture.com
970-641-1747

Sculpture Installation:

1. Secure the 6' lifting straps to the pre-installed lifting points.
2. Compact the subgrade beneath the sculpture.
3. Lift the sculpture using an appropriate reach forklift or crane taking care to equalize the load on straps.
4. Place the sculpture on subgrade and verify layout and all use zones as required by ASTM 1487.
5. Backfill and install resilient surfacing material in accordance with layout guidelines, and ASTM standards.



Plan